



安装尺寸 MOUNTING DIMENSION


MS3011




特点和用途 FEATURES & APPLICATIONS

- ◆ 铝合金材料、IP65
- ◆ 精度高、重心低
- ◆ 容易安装，互换性好
- ◆ 适用于电子秤、汽车衡、平台称等
- ◆ Aluminum alloy material, IP65
- ◆ High precision and low center of gravity
- ◆ Easy to install, good interchangeability
- ◆ Applicable to electronic scale, truck scale, platform scale, etc

受力方式 Load Direction



配线图 Wiring Code



技术参数 TECHNICAL PARAMETERS

参数	Specifications	技术指标/Technique
额定容量	Capacity	20,50,100,200,350 500KG
输出灵敏度	Rated output	2.0±10% mV/V
非线性	Non-linearity	0.00166%F.S.
滞后	Hysteresis	0.00166%F.S.
重复性	Repeatability	0.018%F.S.
蠕变(30min)	Creep(30min)	0.0166%F.S.
温度灵敏度漂移	Temp.effect on output	0.0175%F.S./10℃
零点温度漂移	Temp.effect on zero	0.0125%F.S./10℃
输入电阻	Input impedance	390±5Ω
输出电阻	Output impedance	350±5Ω
绝缘电阻	Insulation	≥5000MΩ/100VDC
激励电压	Excitation Voltage	5~15V
最大激励电压	Maximum excitation Voltage	15V
温度补偿范围	Compensated temp range	-10~40℃
工作温度范围	Operation temp range	-10~50℃
安全超载	Safe overload	150%F.S.
极限超载	Ultimate overload	300%F.S.
电缆线尺寸	Cable size	Φ5x1500mm
材料	Material	aluminum alloy(铝合金)
防护等级	IP Class	IP65
最大秤盘尺寸	Max.platform size	450mmx450mm