



安装尺寸 MOUNTING DIMENSION

MS3056




技术参数 TECHNICAL PARAMETERS

参数	Specifications	技术指标/Technique
额定容量	Capacity	200,500,1000N
精度等级	Accuracy class	C3
输出灵敏度	Rated output	2.0±10% mV/V
零点输出	Zero balance	±2%F.S.
非线性	Non-linearity	0.03%F.S.
滞后	Hysteresis	0.03%F.S.
重复性	Repeatability	0.03%F.S.
蠕变(30min)	Creep(30min)	0.03%F.S.
温度灵敏度漂移	Temp.effect on output	0.05%F.S./10°C
零点温度漂移	Temp.effect on zero	0.05%F.S./10°C
输入电阻	Input impedance	800±10 Ω
输出电阻	Output impedance	800±10 Ω
绝缘电阻	Insulation	≥5000M Ω /100VDC
激励电压	Recommended excitation	5~15V
最大激励电压	Maximum excitation	20V
温度补偿范围	Compensated temp range	-10~40°C
工作温度范围	Operation temp range	-25~70°C
安全超载	Safe overload	150%F.S.
极限超载	Ultimate overload	300%F.S.
电缆线尺寸	Cable size	$\phi 4 \times 3000mm$
材料	Material	aluminum alloy (铝合金)
防护等级	IP Class	IP65
最大秤盘尺寸	Max.platform size	200mmx200mm

特点和用途 FEATURES & APPLICATIONS

- ◆ 铝合金材料
- ◆ 精度高、抗偏载能力强
- ◆ 容易安装，IP65
- ◆ 适用于非标设备测力称重
- ◆ Aluminum alloy material
- ◆ High precision, strong anti-bias load ability
- ◆ Easy to install, IP65
- ◆ Suitable for non- standard equipment force measurement and weighing

受力方式 Load Direction



配线图 Wiring Code

